

Extended Safety Data Sheet
According to Regulation (EC) No 1907/2006, Annex II,
Amended by COMMISSION REGULATION (EU) 2020/878,
According to REGULATION (EC) No 1272/2008

Citric acid

Version 2.0

Issue date: 22-04-2011

Revision date: 12-05-2022

CIRS eSDS Record Number: CSSS-TCO-010-100155

Section 1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

Identification on the label/Trade name: Citric acid
Additional identification: Citric acid monohydrate CAS#5949-29-1
Nanoform is NOT covered by this eSDS.
Identification of the product: CAS#77-92-9 EC#201-069-1
Index Number: 607-750-00-3
REACH registration No.: 01-2119457026-42-0004

1.2 Relevant identified uses of the substance or mixture and uses advised against:

1.2.1 Identified uses:

Use as an intermediate in the production of other organic chemicals.
Formulation into preparations.
Use in personal care products.
Use in detergent/cleaning and other household products.
Use in paper making.
Use in construction products
Use in polymers and plastics products.
Use in the oil industry.
Use in the textile industry.
Use in paints and coatings.
Use in photography products.
Use in laboratory reagents.
Use in water treatment.
Use in the treatment of metal surfaces.
Use in agricultural applications.
Use in medical devices

1.2.2 Uses advised against:

No uses advised against are identified.

1.3 Details of the supplier of the safety data sheet:

Supplier(Only representative): Chemical Inspection & Regulation Service Limited
Supplier(Manufacturer): COFCO BIO-CHEMICAL ENERGY (YUSHU) CO., LTD.
Address: NO.1, Dongfeng Avenue, Wukeshu Economic Development Zone, Changchun
City
Contact person(E-mail): 465687090@qq.com
Telephone: +86-431-83827188
Fax: +86-431-83827050

1.4 Emergency telephone Number:

+86-431-83827188 (Only available during office hours (9:00a.m.-17:30p.m.))

Product name: Citric acid

Version #: 2.0

Issue date: 22-04-2011.

Revision date: 12-05-2022.

eSDS EU
1 / 57

Available outside office hours?

YES

NO

Section 2 Hazards Identification

2.1 Classification of the substance or mixture:

2.1.1 Classification of the substance:

The substance is classified as following according to REGULATION (EC) No 1272/2008:

REGULATION (EC) No 1272/2008	
Hazard classes/Hazard categories	Hazard statement
Eye Irrit. 2	H319
STOT SE 3	H335

For full text of H- phrases: see section 2.2.

2.2 Label elements:

Hazard pictogram(s):



Signal word:

Warning

Hazard statement(s):

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

Precautionary statement(s):

P261: Avoid breathing dust/fume/ gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/ protective clothing/eye protection/face protection/ hearing protection.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTRE/ doctor if you feel unwell.

P337+P313: If eye irritation persists: Get medical advice/attention.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental Hazard information (EU)

Not applicable.

2.3 Other hazards:

The substance is not PBT / vPvB.

The substance is not identified as having endocrine disrupting properties.

Section 3 Composition/information on ingredients

Substance/Mixture:

Substance

Ingredient(s):

Chemical Name	Registration No.	CAS No.	EC No.	Concentration	Specific Concentration limits, M-Factors, Acute Toxicity Estimates (ATE)
Citric acid	01-2119457026-42-0004	77-92-9	201-069-1	>99 % (w/w)	N/A

Section 4 First aid measures

4.1 Description of first aid measures:

In all cases of doubt, or when symptoms persist, seek medical attention.

4.1.1 In case of inhalation:

Get medical aid immediately. Remove from exposure to fresh air immediately.

4.1.2 In case of skin contact:

Wash off with soap and water. If skin irritation persists: Get medical advice/attention.

4.1.3 In case of eyes contact:

Rinse cautiously with water for several minutes as a precaution. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists: Get medical advice/attention.

4.1.4 In case of ingestion:

Drink plenty of water. Do not induce vomiting. Consult a physician if necessary.

4.2 Most important symptoms and effects, both acute and delayed:

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11,

Further symptoms are possible.

4.3 Indication of any immediate medical attention and special treatment needed:

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

If skin irritation or rash occurs, get medical advice/attention.

Section 5 Firefighting measures

5.1 Extinguishing media:

Suitable extinguishing media: Use Water, water spray, dry powder, foam, carbon dioxide (CO₂).

Unsuitable extinguishing media: Not available.

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released: Carbon oxides.

5.3 Advice for firefighters:

Firefighters must wear fire resistant protective equipment. Wear self contained breathing apparatus and protective gloves.

Section 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

6.1.1 For non-emergency personnel: Remove all sources of ignition. Ventilate area of leak or spill.

6.1.2 For emergency responders: Wear appropriate personal protective equipment as specified in section 8.

6.2 Environmental Precautions:

Prevent further leakage or spillage if safe to do so. No special environmental precautions required.

6.3 Methods and material for Containment and Cleaning up:

Pick up and transfer to properly labelled containers. After cleaning, flush away traces with water.

6.4 Reference to other sections:

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

Section 7 Handling and storage

7.1 Precautions for safe handling:

7.1.1 Protective measures: No technical protective measures are required. Take precautionary measures against static discharges.

7.1.2 Advice on general occupational hygiene: Do not eat, drink and smoke in work areas. Wash hands after use.

7.2 Conditions for safe storage, including

Technical measures/Storage conditions: Keep tightly closed in a dry and cool

any incompatibilities:

place.

Incompatible products: Strong oxidizing agents, strong bases.

Packaging material: Polyethylene coated paper bags, Polyvinyl or Polyethylene/propylene big bags.

7.3 Specific end use(s):

Not applicable.

Section 8 Exposure Controls/Personal Protection

8.1 Control parameters:

8.1.1 Occupational exposure limits: Not available.

8.1.2 Additional exposure limits under the conditions of use: Not available.

8.1.3 DNEL/DMEL and PNEC-Values:

Workers - Hazard via inhalation route	Systemic effects-Long term exposure	No hazard identified
Workers - Hazard via dermal route	Systemic effects-Long term exposure	No hazard identified
General Population - Hazard via inhalation route	Systemic effects-Long term exposure	No hazard identified
General Population - Hazard via dermal route	Systemic effects-Long term exposure	No hazard identified
General Population - Hazard via oral route	Systemic effects-Long term exposure	No hazard identified
Hazard for aquatic organisms	Freshwater	No hazard identified
Hazard for aquatic organisms	Marine water	No hazard identified
Hazard for aquatic organisms	STP	No hazard identified
Hazard for aquatic organisms	Sediment (freshwater)	No hazard identified
Hazard for aquatic organisms	Sediment (marine water)	No hazard identified
Hazard for terrestrial organisms	Soil	No hazard identified
Hazard for predators	Secondary poisoning	No potential for bioaccumulation

8.2 Exposure controls:

8.2.1 Appropriate engineering controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

8.2.2 Individual protection measures, such as personal protective equipment:

Eye/face protection: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin protection

Hand protection: Wear appropriate protective rubber gloves to prevent skin exposure.

Body protection: Wear protective gloves and clean body-covering clothing.

Respiratory protection: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use.

Thermal hazards: Wear suitable protective clothing to prevent heat.

8.2.3 Environmental exposure controls: Avoid discharge into the environment. According to local regulations, Federal and official regulations.

Section 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Physical state: Crystalline at 20 °C and 101.3 kPa

Colour: White

Odour: Odourless

Melting/freezing point/range (°C): 153 °C at 1013 hPa

Product name: Citric acid

Version #: 2.0 Issue date: 22-04-2011.

Revision date: 12-05-2022.

eSDS EU
4 / 57

Boiling point or initial boiling point and boiling range (°C):	Not available
Flammability (gas, liquid, solid):	Non flammable
Lower and upper explosion limit:	Not available
Flash point (°C):	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
pH:	Not available
Dynamic viscosity (mm²/s):	Not available
Solubility in water (g/l, 20°C):	592 g/L at 20 °C
Solubility in other polar and non-polar solvents (g/l, 20°C):	Not available
Partition coefficient n-octanol/water (log Po/w, 20°C):	Log Kow (Log Pow): -1.6 to -1.8
Vapour pressure (20°C):	2.2E-6 Pa at 25 °C
Bulk density (kg/m³):	Not available
Relative Density:	1.665 at 20 °C
Relative vapour density:	Not available
Particle characteristics:	D50: 31.9 µm
Evaporation rate:	Not available
Flammability limit - lower (%):	Not available
Ignition temperature (°C):	Not available
Explosive properties:	Non explosive
Oxidising properties:	Oxidising: no
Molecular Formula:	C ₆ H ₈ O ₇
Molecular Weight (g/mol):	192.12 g/mol
9.2. Other information:	
Fat solubility(solvent-oil to be specified) etc:	Not available
Surface tension:	Not available
Dissociation constant in water(pKa):	pKa: 3.13, 4.76 and 6.4 at 25 °C
Oxidation-reduction Potential:	Not available

Section 10 Stability and reactivity

10.1 Reactivity:	The substance is stable under normal storage and handling conditions.
10.2 Chemical stability:	Under normal conditions, the product is stable. No hazardous reaction when handled and stored according to provisions. Hazardous reactions are not known.
10.3 Possibility of hazardous reactions:	Under normal conditions, not hazardous reactions will occur.
10.4 Conditions to avoid:	Incompatible materials. Heat, ignition sources.
10.5 Incompatible materials:	Reactive with oxidizing agents, reducing agents, alkalis.
10.6 Hazardous decomposition products:	Carbon monoxide, carbon dioxide.

Section 11 Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

Acute toxicity:

LD50(Oral, Mouse):	5400 mg/kg bw
LD50(Dermal, Rat):	>2000 mg/kg bw
LC50(Inhalation, Rat):	Not available
Skin corrosion/Irritation:	Not classified
Serious eye damage/irritation:	Causes serious eye irritation.
Respiratory or skin sensitization:	Not classified
Germ cell mutagenicity:	Not classified
Carcinogenicity:	Not classified
Reproductive toxicity:	Not classified
STOT- single exposure:	May cause respiratory irritation. (Affected Organs: Respiratory tract; Route of exposure: Inhalation)
STOT-repeated exposure:	Not classified
Aspiration hazard:	Not classified
11.2 Information on other hazards	
Endocrine disrupting properties	The substance is not identified as having endocrine disrupting properties.
Other information	Not applicable

Section 12 Ecological information

12.1 Toxicity:

Acute (short-term) toxicity:

LC50(96h, Fish):	>100 mg/L
EC50(48h, Daphnia magna):	>50 mg/L
EC50(72h, Algae/aquatic plants):	Not available

Chronic (long-term) toxicity:

NOEC(Fish):	Not available
NOEC(Daphnia magna):	Not available
NOEC(Algae/aquatic plants):	425 (8d)

12.2 Persistence and degradability:

Readily biodegradable.

12.3 Bioaccumulative potential:

Low potential for bioaccumulation.

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment:

The substance is not PBT / vPvB.

12.6 Endocrine disrupting properties:

The substance is not identified as having endocrine disrupting properties.

12.7 Other adverse effects:

Not available

12.8 Additional information

Not available.

Section 13 Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with all applicable local and national regulations. Use recovery/recycling where feasible, otherwise incineration is the recommended method of disposal. Empty containers may contain hazardous residues. Do not cut, puncture or weld on or near to the container. Labels should not be removed from containers until they have been cleaned. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers.

Section 14 Transport information

	Land transport (ADR/RID)	Inland waterways (ADN)	Sea transport (IMDG)	Air transport (ICAO/IATA)
14.1 UN number or ID number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN Proper shipping name	Not regulated	Not regulated	Not regulated	Not regulated
14.3 Transport hazard Class(es)	Not regulated	Not regulated	Not regulated	Not regulated
14.4 Packing group	Not regulated	Not regulated	Not regulated	Not regulated
14.5 Environmental hazards	No	No	No	No
14.6 Special precautions for user	See section 2.2	See section 2.2	See section 2.2	See section 2.2
14.7 Maritime transport in bulk according to IMO instruments	Not regulated	Not regulated	Not regulated	Not regulated

Section 15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Relevant information regarding authorization:

Not applicable.

Relevant information regarding restriction:

Not applicable.

Other EU regulations:

Employment restrictions concerning young person must be observed. For use only by technically qualified individuals.

Other National regulations:

Not applicable

15.2 Chemical safety assessment

YES

NO

Section 16 Other information

16.1 Indication of changes:

Version 1.0 Amended by (EU) 2020/878

Version 2.0 Exposure scenarios are placed after section 16.

16.2 Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation for rail International transportation of Dangerous goods

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: Code international maritime dangerous goods code

ICAO: International Civil Aviation Organization

IATA: International Air Transport Association

LC50: median lethal concentration

EC50: The effective concentration of substance that causes 50% of the maximum response.

NOEC: No Observed Effect Concentration

DNEL: derived no-effect level

PNEC: predicted no-effect concentration

16.3 Key literature references and sources for data

ECHA Registered substances data

16.4 Classification and procedure used to derive the classification for mixtures according to Regulation (EC)

1272/2008 [CLP]

Classification according to Regulation (EC) No. 1272/2008		Classification procedure
Eye Irrit. 2	H319	On basis of test data
STOT SE 3	H335	On basis of test data

16.5 Relevant H-statements (number and full text):

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

16.6 Training instructions:

Not applicable.

16.7 Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

16.8 Notice to reader:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgment of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Author: Hangzhou REACH Technology Group Co., Ltd. **Website:** www.cirs-group.com **Tel:** 0571-87206555 **Email:** info@cirs-group.com

Annex to extended safety data sheet (eSDS)

Exposure scenario

Substance / User identity				
	Registration number(s) 01-2119457026-42-0004			
	Substance identity CAS#77-92-9; EC#201-069-1			
1	Short title of the exposure scenario 1. Production of citric acid			
	Processes and activities covered by the exposure scenario PROC 1, PROC 2, PROC 3, PROC 4, PROC 8b, SU 3, SU 8,			
2	Operational conditions and risk management measures			
	Duration an frequency of use			
	Worker All applicable PROCs	>4h		
	Physical form of substance:	Solid.		
	Concentration of substance in preparation or article	90%		
	Other relevant operational conditions of use	<p>No measured data are available for releases of citric acid to air and waste water for the generic production site. Releases are therefore estimated on the basis of other information.</p> <p>Releases to air: Due to the very low vapour pressure of the key intermediates and of citric acid itself, losses to air are considered to be zero.</p> <p>Releases to waste water: The key production stage is the precipitation of calcium citrate. This substance is of low solubility, although a small quantity of citric acid could remain dissolved, a fraction of 0.0001, or 2.86 kg/d over 350 days.</p> <p>There could be losses during handling and packaging processes, but when around 30 tonnes per day are handled these processes are highly automated. It can be anticipated that occasional spillages can occur due to small levels of leakage, amounting to at most 1 kg per day passing to aqueous waste.</p> <p>The total passing to aqueous waste water is 3.86 kg/d.</p>		
Risk management measures:				
2.1	Control of worker exposure			
	Operational conditions related to respiration and skin contact	Information type	Data field	Explanation
		Respiration volume under conditions of use	10 m ³ /d	Default for workers, light activity
		Area of skin contact with the substance under conditions of use	240 cm ²	ECETOC TRA default:
			480 cm ²	PROC 1: palm of one hand
			240 cm ²	PROC 2: palms of both hands
			480 cm ²	PROC 3: palm of one hand
480 cm ²	PROC4: palms of both hands			
480 cm ²	PROC8b: palms of both hands			
Body weight	70 kg	Default		
Technical fate of substance and losses from process/use to waste, waste water and air	Information type	Data field	Explanation	
	Fraction of applied amount lost from process/use to waste gas	0 kg/kg	See text	

		Fraction of applied amount lost from process/use to waste water	0.0001 kg/kg	See text
Engineering controls:				
Personal protective equipment (PPE)	Information type	Data field	Explanation	
	Containment plus good work practice required	Yes		
	Local exhaust ventilation required plus good work practise	Yes	Typical practice of chemical industry. Not applicable for PROC1.	
	Skin protection	Protective gloves		
	Eye protection	Safety glasses		
	Respiratory protection	Dust mask. In case of open handling of larger quantities or accidental release: particle mask or respirator with independent air supply		
	Clothing	Working clothing worn.		
Risk management measures related to environmental emissions from industrial sites	Information type	Data field	Explanation	
	Onsite pre-treatment of waste water	Yes	Neutralisation	
	Resulting fraction of initially applied amount in waste water released from site to the external sewage system		On-site biological waste treatment is expected to remove a high proportion of citric acid, as the substance is highly biodegradable.	
	Air emission abatement	No measured data		
	Resulting fraction of applied amount in waste gas released to environment	No measured data		
	Onsite waste treatment	No measured data	Secondary biological treatment	
	Fraction of initially applied amount	No measured data		

		sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment.		
		Municipal or other type of external waste water treatment	None	None
		Effluent (of the waste water treatment plant) discharge rate	1 x 10 ⁷ l/d	Default for a large industrial site
		Recovery of sludge for agriculture or horticulture	Yes	Dried sludge may be sold as an approved agricultural fertiliser

Frequency and duration of use

Information type	Data field	Explanation
Used amount of substance per day	30 tonnes	
Duration of exposure per day at workplace [for one worker]	>4 hours (all PROCs)	REACH default used as a worst-case; actual exposure times may be significantly less.
Frequency of exposure at workplace [for one worker]	Once per day	
Annual amount used per site	10,000 tonnes	
Emission days per site	350	

Use per site
Duration of emission
Waste water flow
Dilution factor

Information on estimated exposure and Downstream-user guidance

3	Exposure estimation and reference to its source:
	Occupational exposure:

Dermal exposure estimates (based on ECETOC TRA model)	Process category	Description	LEV present?	Predicted exposure ($\mu\text{g}/\text{cm}^2/\text{day}$)	Exposed skin surface area (cm^2)	Dermal exposure ($\text{mg}/\text{kg}/\text{day}$) ^a
	PROC1	Use in closed process, no likelihood of exposure	No	100	240	0.3
	PROC2	Use in closed, continuous process with occasional controlled exposure (e.g. sampling)	Yes	20	480	0.14
	PROC3	Use in closed batch process (synthesis or formulation)	Yes	10	240	0.03
	PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	100	480	0.69
	PROC8b	Transfer from/to large vessels (dedicated)	Yes	100	480	0.69
	<p>a) Calculated assuming a default bodyweight of 70 kg for worker.</p> <p>b) In the ECETOC TRA model, LEV is not considered relevant for PROC1.</p>					

Inhalation exposure estimates (based on ECETOC TRA model)	Process category	Description	LEV present?	Predicted exposure (ppm)	Predicted exposure (mg/m ³) ^c	Inhalation exposure (mg/kg/day) ^d
	PROC1	Use in closed process, no likelihood of exposure	No ^b	0.001	0.01	0.001
	PROC2	Use in closed, continuous process with occasional controlled exposure (e.g. sampling)	Yes	0.01	0.1	0.01
	PROC3	Use in closed batch process (synthesis or formulation)	Yes	0.01	0.1	0.01
	PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	0.31	2.5	0.36
	PROC8b	Transfer from/to large vessels(dedicated)	Yes	0.16	1.25	0.18
	<p>b) In the ECETOC TRA model, LEV is not considered relevant for PROC1.</p> <p>c) Results are calculated as mg/m³ for solids and ppm for non-solids</p> <p>d) Calculated assuming a default bodyweight of 70 kg for workers and a default respiratory volume of 10 m³, light activity, for an 8 hour work shift</p>					

Summary of long-term exposure concentration to workers	Routes of exposure	Concentrations	Justification
	Dermal local exposure (in µg/cm ²)	0.6	ECETOC TRA prediction for PROC8b, multiplied by an uptake factor of 0.006.
	Dermal systemic exposure (in mg/kg bw/d)	0.004	ECETOC TRA prediction for PROC8b, multiplied by an uptake factor of 0.006.
	Inhalation exposure (in mg/m ³)/8h workday	2.5	ECETOC TRA prediction for PROC8b
	Inhalation exposure (in mg/kg/d)/8h workday	0.36	ECETOC TRA prediction for PROC8b

4	Environmental releases	
Predicted environmental release	<p>Predicted environmental release estimates have been used for releases during production. No measured data are available for the concentration of citric acid in any environmental compartment. The releases have been estimated using the exposure scenario for production (section 9.1.1.2 and 9.1.1.6) and Predicted Environmental Concentrations have been determined using EUSES 2.1.1. The EUSES program implements the environmental exposure models described in REACH Technical Guidance Chapter R16. Default model parameters have been used unless stated below.</p> <p>The basis of local and regional production tonnages is to consider the sizes of the largest sites in the EU relative to the total tonnage as follows: Production volume in EU: 100 000 tonnes Regional tonnage: 10 000 tonnes Fraction of main local source: 1 Local tonnage: 29 tonnes per day Number of days: 350</p> <p>The contribution of local releases to the regional concentration has been considered using the appropriate calculation in EUSES 2.1.1.</p>	

Summary of Predicted Exposure Concentrations		PEC	unit
	AIR		
	Annual average local PEC in air (total)	3.50 x 10 ⁻¹⁶	[mg m ⁻³]
	WATER, SEDIMENT		
	Local PEC in surface water during emission episode (dissolved)	0.0153	[mg l ⁻¹]
	Annual average local PEC in surface water (dissolved)	0.0153	[mg l ⁻¹]
	Local PEC in fresh-water sediment during emission episode	0.261	[mg kg wwt ⁻¹]
	Local PEC in seawater	1.80 x 10 ⁻³	[mg l ⁻¹]

		during emission episode (dissolved)		
		Annual average local PEC in seawater (dissolved)	1.78×10^{-3}	[mg l ⁻¹]
		Local PEC in marine sediment during emission episode	0.0307	[mg kg wwt ⁻¹]
		SOIL, GROUNDWATER		
		Local PEC in agric. soil (total) averaged over 30 days	0.0227	[mg kg wwt ⁻¹]
		Local PEC in agric. soil (total) averaged over 180 days	7.43×10^{-3}	[mg kg wwt ⁻¹]
		Local PEC in grassland (total) averaged over 180 days	2.97×10^{-3}	[mg kg wwt ⁻¹]
		Local PEC in pore water of agricultural soil	1.12×10^{-4}	[mg l ⁻¹]
		Local PEC in pore water of grassland	4.48×10^{-5}	[mg l ⁻¹]
		Local PEC in groundwater under agricultural soil	1.12×10^{-4}	[mg l ⁻¹]

Substance / User identity				
Registration number(s)	01-2119457026-42-0004			
Substance identity	CAS#77-92-9; EC#201-069-1			
1	Short title of the exposure scenario	2. Use of citric acid as a chemical intermediate		
	Processes and activities covered by the exposure scenario	SU3 (Industrial uses), SU8, SU9, PROC 1, PROC 2, PROC 3, PROC 4, PROC 8b,		
2	Operational conditions and risk management measures			
	Duration an frequency of use			
	Worker All applicable PROCs	>4h		
	Physical form of substance:	solid		
	Concentration of substance in preparation or article			
	Other relevant operational conditions of use			
Risk management measures:				
2.1	Control of worker exposure			
	Containment and local exhaust ventilation	Information type	Data field	Explanation
		Containment plus good work practice required	Yes	
		Local exhaust ventilation required plus good work practise	Yes	Typical practice of chemical industry. Not applicable for PROC1.
	Personal protective equipment (PPE)	Information type	Data field	Explanation
		Skin protection	Protective gloves	
		Eye protection	Safety glasses	
		Respiratory protection	Dust mask. In case of open handling of larger quantities or accidental release: particle mask or respirator with independent air supply	
		Clothing	Working clothing worn.	
	Risk management measures related to environmental emissions from industrial sites:	Information type	Data field	Explanation
		Onsite pre-treatment of waste water	Yes	Neutralisation
		Resulting fraction of initially applied amount in waste		On-site biological waste treatment is expected to

		water released from site to the external sewage system		remove a high proportion of citric acid, as the substance is highly biodegradable.	
		Air emission abatement	No measured data		
		Resulting fraction of applied amount in waste gas released to environment	No measured data		
		Onsite waste treatment	No measured data	Secondary biological treatment	
		Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment.	No measured data		
		Municipal or other type of external waste water treatment	None	None	
		Effluent (of the waste water treatment plant) discharge rate	1x 10 ⁷ l/d	Default for a large industrial site	
		Recovery of sludge for agriculture or horticulture	Yes	Dried sludge may be sold as an approved agricultural fertiliser	
2.2	Control of environmental exposure				
	Frequency and duration of use				
	Duration, frequency and amount	Information type	Data field	Explanation	
		Used amount of substance per day	10,000 kg/d	Generic information	
		Duration of exposure per day at workplace [for one worker]	>4 hours (all PROCs)	REACH default used as a worst case; actually exposure times may be significantly less	

		Frequency of exposure at workplace [for one worker]	Once per day	In situations where the duration of exposure is lower, frequency of exposure may be higher
		Annual amount used per site	3,000 tpa	Generic information
		Emission days per site	300 d/y	REACH default number of days for high volumes
Other operational conditions of use				
	Releases to air	Due to the very low vapour pressure of the key intermediates and of citric acid itself, losses to air are considered to be zero.		
	Releases to water	The REACH ERC 6A (Industrial use of intermediate) release default estimates to waste water is 2%.		
	Technical conditions and measures at process level (source) to prevent release	No specific measures are considered		
	Technical onsite conditions and measures to reduce or limit discharges, air emissions	<p>The default TGD (TGD ESD part IV) release rate from processing of synthetic intermediate is 0.7% by weight for a wet process and 0% for a dry (water-free) process. Processing of citric acid is a wet-process. On-site waste water treatment at the plant (e.g. activated carbon, precipitation and so on) is already included in the emission factors.</p> <p>The default loss of 70 kg/d (EU TGD 0.7% default) from the processing of 30 t/d of citric acid is not considered to be realistic. Realistic losses to waste water from the processing of citric acid at a typical industrial site are expected to come from:</p> <ul style="list-style-type: none"> • Substance washout from ventilation systems • Minor routine spillages • Occasional equipment loss/leakages <p>Given that a solid is precipitated efficiently it is considered that 7 kg/d is a more realistic estimate.</p> <p>Citric acid is highly degradable and on-site waste water treatment is expected to mean that little of the substance is released to the wider environment.</p> <p>It can be assumed that this process will be taking place at a large industrial site with waste water passing to a larger-than-default WWTP with a flow rate of 10,000 m³/day.</p>		
	Technical fate of substance and losses from process/use to waste, waste water and air	Information type	Data field	Explanation
		Fraction of applied amount lost from process/use to waste gas	0 kg/kg	See text
		Fraction of applied amount lost from process/use to waste water	0.007 kg/kg	See text
Information on estimated exposure and Downstream-user guidance				
3	Exposure estimation and reference to its source:			

Dermal	Process category	Description	Dermal exposure?	Predicted exposure ($\mu\text{g}/\text{cm}^2/\text{day}$)	Exposed skin surface area (cm^2)	Dermal exposure ($\text{mg}/\text{kg}/\text{day}$) ^a
	PROC1	Use in closed process, no likelihood of exposure	Yes	100	240	0.3
	PROC2	Use in closed, continuous process with occasional controlled exposure	Yes	20	480	0.14
	PROC3	Use in closed batch process (synthesis or formulation)	Yes	10	240	0.03
	PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	100	480	0.69
	PROC8b	Transfer from/to large vessels (dedicated)	Yes	100	480	0.69
	<p>a) Calculated assuming a default bodyweight of 70 kg for worker</p> <p>b) In the ECETOC TRA model, LEV is not considered relevant for PROC1.</p>					
Inhalation	Process category	Description	LEV present?	Predicted exposure (ppm)	Predicted exposure (mg/m^3) ^c	Inhalation Exposure ($\text{mg}/\text{kg}/\text{day}$) ^d
	PROC1	Use in closed process, no likelihood of exposure	No ^b	0.001	0.01	0.001
	PROC2	Use in closed, continuous process with occasional controlled exposure	Yes	0.01	0.1	0.01
	PROC3	Use in closed batch process (synthesis or formulation)	Yes	0.01	0.1	0.01
	PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	0.31	2.5	0.36
	PROC8b	Transfer from/to large vessels (dedicated)	Yes	0.16	1.25	0.18
<p>b) In the ECETOC TRA model, LEV is not considered relevant for PROC1.</p> <p>c) Results are calculated as mg/m^3 for solids and ppm for non-solids</p> <p>d) Calculated assuming a default bodyweight of 70 kg for workers and a default respiratory volume of 10 m^3, light activity, for an 8 hour work shift</p>						
long-term exposure concentration to workers	Routes of exposure	Concentrations		Justification		
	Dermal local exposure (in $\mu\text{g}/\text{cm}^2$)	0.6		ECETOC TRA prediction for PROC8b, multiplied by an uptake factor of 0.006.		

		Dermal systemic exposure (in mg/kg bw/d)	0.004	ECETOC TRA prediction for PROC8b, multiplied by an uptake factor of 0.006.
		Inhalation exposure (in mg/m ³)/8h workday	2.5	ECETOC TRA prediction for PROC8b
		Inhalation exposure (in mg/kg/d)/8h workday	0.36	ECETOC TRA prediction for PROC8b
Predicted Environmental Concentrations			PEC	unit
	AIR			
	Annual average local PEC in air (total)		5.45 x 10 ⁻¹⁶	[mg m ⁻³]
	WATER, SEDIMENT			
	Local PEC in surface water during emission episode (dissolved)		0.0154	[mg l ⁻¹]
	Annual average local PEC in surface water (dissolved)		0.0154	[mg l ⁻¹]
	Local PEC in fresh-water sediment during emission episode		0.263	[mg kg wwt ⁻¹]
	Local PEC in seawater during emission episode (dissolved)		0.0084	[mg l ⁻¹]
	Annual average local PEC in seawater (dissolved)		0.00716	[mg l ⁻¹]
	Local PEC in marine sediment during emission episode		0.144	[mg kg wwt ⁻¹]
	SOIL, GROUNDWATER			
	Local PEC in agric. soil (total) averaged over 30 days		0.0411	[mg kg wwt ⁻¹]
	Local PEC in agric. soil (total) averaged over 180 days		0.0135	[mg kg wwt ⁻¹]
	Local PEC in grassland (total) averaged over 180 days		0.00539	[mg kg wwt ⁻¹]
	Local PEC in pore water of agricultural soil		0.000203	[mg l ⁻¹]

		Local PEC in pore water of grassland	0.0000813	[mg l ⁻¹]
		Local PEC in groundwater under agricultural soil	0.000203	[mg l ⁻¹]

Substance / User identity				
	Registration number(s)	01-2119457026-42-0004		
	Substance identity	CAS#77-92-9; EC#201-069-1		
1	Short title of the exposure scenario	3. Formulation of citric acid into preparations		
	Processes and activities covered by the exposure scenario	SU3, 10, SU5, SU13, 20 PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC19 PC35 , PC39		
2	Operational conditions and risk management measures			
	Duration an frequency of use			
	Worker All applicable PROCs	>4h		
	Physical form of substance:	solid		
	Concentration of substance in preparation or article			
	Other relevant operational conditions of use	<p>The citrates used in the formulation of products are generally solids which may be mixed with other solids or dissolved in aqueous solution. There is some potential for airborne release of citric acid (or citrate) particulates on charging (transfer, dosing) to the process equipment used, especially if containment is not good. However, the most likely release will be to waste water via clean out or spillage.</p> <p>Taking the HERA figure of approx. 100 000 tpa [HERA, 2005] for total use of citrates in detergents, and realistic values of 10% formulated in a single region, and 60% of that at a single location, gives a volume of 6,000 tpa citrates formulated at a single location.</p> <p>For this generic site, the daily loss rate to waste water is $6000 \text{ t} \times 1000 \text{ kg/t} \times 0.0009 / 300 \text{ d} = 18 \text{ kg/d}$.</p> <p>The tonnage to be covered is now 150 000 tpa, but the site size is retained. The loss rate is considered to be a reasonable worst case for a large site. At smaller formulation sites the amount handled per day would be lower and the controls could be less, but overall rates per day would be similar.</p>		
Risk management measures:				
2.1	Control of worker exposure			
	Containment and local exhaust ventilation	Information type	Data field	Explanation
		Containment plus good work practice required	Yes	General good hygiene and housekeeping
		Local exhaust ventilation required plus good work practice.	Yes	Typical practice of chemical industry.
	Personal protective equipment (PPE)	Information type	Data field	Explanation
		Skin protection	Protective gloves	
		Eye protection	Safety glasses	
		Clothing	Working clothing worn.	
	Risk management measures related to environmental emissions from industrial sites:	Information type	Data field	Explanation
		Onsite pre-treatment of waste water	Yes	Removal of solids in settling tanks
		Resulting fraction of initially applied amount in waste water released from site to the external sewage system	No measured data	

		Air emission abatement	No measured data	
		Resulting fraction of applied amount in waste gas released to environment	No measured data	See text
		Onsite waste treatment	No	Worst-case assumption as no specific information available.
		Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment.	No measured data	
		Municipal or other type of external waste water treatment	Yes	Typical practise in the chemical industry
		Effluent (of the waste water treatment plant) discharge rate	1 * 10 ⁷ L/d	Default for a large industrial site.
		Recovery of sludge for agriculture or horticulture	Yes	Worst-case assumption as no specific information available.
2.2	Control of environmental exposure			
	Frequency and duration of use			
	Duration, frequency and amount	Information type	Data field	Explanation
		Used amount of substance per day	6000 tonnes	
		Duration of exposure per day at workplace [for one worker]	>4 hours (all PROCs)	For some applications/setting exposure times may be significantly less
		Frequency of exposure at workplace [for one worker]	Once per day	For some applications/settings with shorter duration exposures, multiple exposures may occur in a single day
		Annual amount used per site	20 tonnes	
		Emission days per site	300 days	
Information on estimated exposure and Downstream-user guidance				
3	Exposure estimation and reference to its source:			
	Occupational exposure:			

Dermal	Process category	Description	Dermal exposure?	Predicted exposure ($\mu\text{g}/\text{cm}^2/\text{day}$)	Exposed skin surface area (cm^2)	Dermal exposure ($\text{mg}/\text{kg}/\text{day}$) ^a
	PROC1	Use in closed process, no likelihood of exposure	Yes	100	240	0.3
	PROC2	Use in closed, continuous process with occasional controlled exposure (e.g. sampling)	Yes	20	480	0.14
	PROC3	Use in closed batch process (synthesis or formulation)	Yes	10	240	0.034
	PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	100	480	0.69
	PROC5	Mixing or blending in batch processes (multistage and/or significant contact)	Yes	200	480	1.37
	PROC7	Industrial spraying	Yes	200	1500	4.29
	PROC8a	Transfer from/to large vessels (non-dedicated).	Yes	100	960	1.37
	PROC8b	Transfer from/to large vessels (dedicated)	Yes	100	480	0.69
	PROC9	Transfer to small containers	Yes	100	480	0.69
	PROC13	Treatment of articles by dipping and pouring	Yes	100	480	0.69
	PROC14	Production of preparations or articles by tableting, compression, extrusion, pelletisation	Yes	50	480	0.34
	PROC15	Use of laboratory reagents in small scale laboratories	Yes	10	240	0.034
PROC19	Hand-mixing with intimate contact (only	Yes	500	1980	14.1	

		PPE available				
Inhalation	Process category	Description	LEV present ?	Predicted exposure (ppm)	Predicted exposure (mg/m ³) ^c	Inhalation Exposure (mg/kg/day) ^d
	PROC1	Use in closed process, no likelihood of exposure	No ^b	0.0013	0.01	0.0014
	PROC2	Use in closed, continuous process with occasional controlled exposure (e.g. sampling)	Yes	0.0125	0.1	0.014
	PROC3	Use in closed batch process (synthesis or formulation)	Yes	0.0125	0.1	0.014
	PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	0.31	2.5	0.36
	PROC5	Mixing or blending in batch processes (multistage and/or significant contact)	Yes	0.31	2.5	0.36
	PROC7	Industrial spraying	Yes	1.25	10	1.43
	PROC8a	Transfer from/to large vessels (non-dedicated)	Yes	0.63	5	0.71
	PROC8b	Transfer from/to large vessels (dedicated)	Yes	0.31	2.5	0.36
	PROC9	Transfer to small containers	Yes	0.25	2	0.29
	PROC13	Treatment of articles by dipping and pouring	Yes	0.0013	0.01	0.0014
	PROC14	Production of preparations or articles by tableting, compression, extrusion,	Yes	0.13	1	0.14

			pelletisation				
		PROC15	Use of laboratory reagents in small scale laboratories	Yes	0.063	0.5	0.071
		PROC19	Hand-mixing with intimate contact (only PPE available)	Yes	0.0063	0.05	0.0071
		<p>b) Results are calculated as mg/m³ for solids and ppm for non-solids</p> <p>c) Calculated assuming a default bodyweight of 70 kg for workers and a default respiratory volume of 10 m³, light activity, for an 8 hour work shift</p>					
	long-term exposure concentration to workers	Routes of exposure	Concentration	Justification			
		Dermal local exposure (in µg/cm ²)	3	ECETOC TRA prediction for PROC19, multiplied by an uptake factor of 0.006.			
		Dermal systemic exposure (in mg/kg bw/d)	0.08	ECETOC TRA prediction for PROC19, multiplied by an uptake factor of 0.006.			
		Inhalation exposure (in mg/m ³)/8h workday	10	ECETOC TRA prediction for PROC7			
		Inhalation exposure (in mg/kg/d)/8h workday	1.43	ECETOC TRA prediction for PROC7			
	Predicted Exposure Concentrations (PEC)		PEC	unit			
		AIR					
		Annual average local PEC in air (total)	1.4 x 10 ⁻¹⁵	[mg.m ⁻³]			
		WATER, SEDIMENT					
		Local PEC in surface water during emission episode (dissolved)	0.0158	[mg l ⁻¹]			
		Annual average local PEC in surface water (dissolved)	0.0157	[mg l ⁻¹]			
		Local PEC in fresh-water sediment during emission episode	0.27	[mg kg wwt ⁻¹]			
		Local PEC in seawater during emission episode (dissolved)	0.0194	[mg l ⁻¹]			
		Annual average local PEC in seawater (dissolved)	0.0162	[mg l ⁻¹]			
		Local PEC in marine sediment during emission episode	0.331	[mg kg wwt ⁻¹]			

SOIL, GROUNDWATER		
Local PEC in agric. soil (total) averaged over 30 days	0.106	[mg kg wwt ⁻¹]
Local PEC in agric. soil (total) averaged over 180 days	0.347	[mg kg wwt ⁻¹]
Local PEC in grassland (total) averaged over 180 days	0.0139	[mg kg wwt ⁻¹]
Local PEC in pore water of agricultural soil	5.23 x 10 ⁻⁴	[mg l ⁻¹]
Local PEC in pore water of grassland	2.09 x 10 ⁻⁴	[mg l ⁻¹]
Local PEC in groundwater under agricultural soil	5.23 x 10 ⁻⁴	[mg l ⁻¹]

Substance / User identity		
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	4. Personal care use
	Processes and activities covered by the exposure scenario	SU20,SU21,SU22, PROC 10, PROC 11, PROC 19 PC35 , PC39
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	solid
	Concentration of substance in preparation or article	
	Other relevant operational conditions of use	<p>The EU TGD A-Table A4.1 gives the releases of cosmetics to air and wastewater as 0 and 100% respectively. This seems reasonable, given that citrates are non-volatile and highly water soluble. It is also in agreement with Colipa's assessment of the fate of non-volatile components of cosmetics (Colipa 2008).</p> <p>The TGD defaults and REACH environmental release category (ERC8a) assume that if a substance is used widely across the EU, the fraction of the production volume used in the standard EU Region is 10%. For cosmetics, the fraction of the main local source (fmainsource) is 0.0005 (HERA, 2005, page 27). This is equivalent to saying that use in a region is evenly distributed. The number of days of use is 365 per year. Therefore, for 7500 tpa of citric acid in personal care products used widely across the EU, the estimated release of citric acid to a particular default-sized local waste water treatment plant is at most:</p> $7\ 500\ 000\ \text{kg/y} \times 0.1 \times 0.0005 / 365\ \text{d/y} = 1.03\ \text{kg/d}$
Risk management measures:		
2.1	Control of worker exposure	
	Technical conditions and measures at process level (source) to prevent release	No risk management measures are possible for personal care use in respect of the environment.
	Technical conditions and measures to control dispersion from source towards the worker	No risk management measures are possible for personal care use in respect of the environment.
	Engineering controls:	No risk management measures are possible for personal care use in respect of the environment.
	Organisational measures to prevent/limit releases, dispersion and exposure	No risk management measures are possible for personal care use in respect of the environment.
	Conditions and measures related to personal protection, hygiene and health evaluation	No risk management measures are possible for personal care use in respect of the environment.
Information on estimated exposure and Downstream-user guidance		
3	Environmental releases	Predicted Environmental Concentrations have been determined using EUSES 2.1.1. The EUSES program implements the environmental exposure models described in REACH Technical Guidance Chapter R16. Default model parameters have been used

with the following exceptions:
 The basis of local and regional production tonnages is to consider the sizes of the largest sites in the EU relative to the total tonnage as follows:
 Production volume in EU: 7,500,000 tonnes
 Regional tonnage: 750,000 tonnes
 Fraction of main local source: 0.0005
 Local tonnage: 1.03 tonnes per day
 Number of days: 365

The contribution of local releases to the regional concentration has been considered using the appropriate calculation in EUSES 2.1.1. Table 9.33 shows the Predicted Environmental Concentrations. Due to the ready-biodegradability of citric acid it has not been considered necessary to define a PEC. The low log Kow and ready biodegradability indicate that bioaccumulation is not a concern for citric acid. Therefore, the assessment of secondary poisoning is not considered further.

Summary of Predicted Exposure Concentrations

	PEC	unit
AIR		
Annual average local PEC in air (total)	5.45 x 10 ⁻¹⁶	[mg.m ⁻³]
WATER, SEDIMENT		
Local PEC in surface water during emission episode (dissolved)	1.59 x 10 ⁻²	[mg l ⁻¹]
Annual average local PEC in surface water (dissolved)	1.59 x 10 ⁻²	[mg l ⁻¹]
Local PEC in fresh-water sediment during emission episode	2.71 x 10 ⁻¹	[mg kg wwt ⁻¹]
Local PEC in seawater during emission episode (dissolved)	1.48 x 10 ⁻³	[mg l ⁻¹]
Annual average local PEC in seawater (dissolved)	1.48 x 10 ⁻³	[mg l ⁻¹]
Local PEC in marine sediment during emission episode	2.53 x 10 ⁻²	[mg kg wwt ⁻¹]
SOIL, GROUNDWATER		
Local PEC in agric. soil (total) averaged over 30 days	3.02 x 10 ⁻²	[mg kg wwt ⁻¹]
Local PEC in agric. soil (total) averaged over 180 days	9.89 x 10 ⁻³	[mg kg wwt ⁻¹]
Local PEC in grassland (total) averaged over 180 days	3.95 x 10 ⁻³	[mg kg wwt ⁻¹]
Local PEC in pore water of agricultural soil	1.49 x 10 ⁻⁴	[mg l ⁻¹]
Local PEC in pore water of grassland	5.97 x 10 ⁻⁵	[mg l ⁻¹]

		Local PEC in groundwater under agricultural soil	1.49 x 10 ⁻⁴	[mg l ⁻¹]
	Other environmental releases	<p>The EUSES model uses the Simple Treat sewage treatment model to predict the fate of a substance in the STP, based on the physicochemical and biodegradation properties. For citric acid, SimpleTreat predicts the following:</p> <p>12.6 % to water:</p> <p>0.112 % to air:</p> <p>0.0154 % to sludge:</p> <p>87.3 % degraded.</p> <p>Sludge from WWTPs may be spread on agricultural soil.</p> <p>The dilution factor of 900 and 1000 (in the receiving water) have been applied for fresh water and marine water respectively, as there is no information on specific hydrodynamic conditions.</p> <p>There is no direct release to the terrestrial compartment on a local scale as biosludge from on-site waste water treatment is disposed of via incineration or landfill. However, due to use of municipal WWTP by some EU production sites, spreading of sludge on agricultural soil is included as a reasonable worst case.</p>		

Substance / User identity				
	Registration number(s) 01-2119457026-42-0004			
	Substance identity CAS#77-92-9; EC#201-069-1			
1	Short title of the exposure scenario 5. Use of citric acid in cleaning products			
	Processes and activities covered by the exposure scenario SU3, SU21, SU22, PROC1, PROC 2, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 11, PROC 13, PROC 19 PC35			
2	Operational conditions and risk management measures			
	Duration an frequency of use			
	Worker All applicable PROCs >4h			
	Physical form of substance: under conditions of use it is used as a liquid. May be liquid or solid.			
	Concentration of substance in preparation or article			
	Other relevant operational conditions of use No measured data are available for releases to air and waste water during the use of citric acid in cleaning products. Releases are therefore estimated on the basis of information in the public domain. Citric acid and citrates are used in a variety of cleaning products but generally in aqueous solution. The most likely release route will, therefore, be to waste water via rinsing to drain in-use, spillage, clean out or discharge of cleaning baths or liquors. Indeed, releases to waste water can be assumed to be 100%, since all the citric acid/citrate will eventually be washed to drain. This may be an overestimate since it does not allow for any of the substance to be either released to air (extremely unlikely) during the process or to adsorb to a surface on drying or to a cleaning implement (e.g., cloth) which may be landfilled. The release of citrates from use in cleaning products in industrial, professional and consumer use can be estimated. The TGD defaults and REACH environmental release category (ERC8a) assume that if a substance is used widely across the EU, the fraction of the production volume used in the standard EU Region is 10%. For cleaning products, the fraction of the regional tonnage discharging to a particular waste water treatment plant can be estimated as 0.0005 (HERA, 2005). The number of days of use is 365 per year. Therefore, for 100,000 tpa of citric acid in cleaning products used widely across the EU, the estimated release of citrates to a particular default-sized local waste water treatment plant is at most: $100,000,000 \text{ kg/y} \times 0.1 \times 0.0005 / 365 \text{ d/y} = 13.7 \text{ kg/d}$ = (Amount of citrates used in cleaning products per year x fraction to water x fraction in the region x fraction of main local source) / number of days per year The research carried out by the HERA project was thorough and accepted by the EU authorities as valid.			
Risk management measures:				
2.1	Control of worker exposure			
	Containment and local exhaust ventilation	Information type	Data field	Explanation
		Containment plus good work practice required	Yes	General good hygiene and housekeeping
Local exhaust ventilation required plus good work practise	No			

Personal protective equipment (PPE)	Information type	Data field	Explanation
	Skin protection	Protective gloves	
	Eye protection	Safety glasses	
	Clothing	Working clothing worn.	
Other risk management measures related to workers	N/A		
Risk management measures related to environmental emissions from industrial sites	Information type	Data field	Explanation
	Onsite pre-treatment of waste water	Yes	Neutralisation
	Resulting fraction of initially applied amount in waste water released from site to the external sewage system		On-site biological waste treatment is expected to remove a high proportion of citric acid, as the substance is highly biodegradable.
	Air emission abatement	No measured data	
	Resulting fraction of applied amount in waste gas released to environment	No measured data	
	Onsite waste treatment	No measured data	Secondary biological treatment
	Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment.	No measured data	
	Municipal or other type of external waste water treatment	None	None
	Effluent (of the waste water treatment plant) discharge rate	2000000 l/d	Default for a standard WWTP
	Recovery of sludge for agriculture or horticulture	Yes	Dried sludge may be sold as an approved agricultural fertiliser
Onsite pre-treatment of waste water	Yes	Neutralisation	
2.2	Control of environmental exposure		
	Frequency and duration of use		
Duration, frequency and amount	Information type	Data field	Explanation
	Used amount of substance per day	200,000 kg/d	Generic information
	Duration of exposure per day at workplace [for one worker]	>4 hours (all PROCs)	For some applications/setting exposure times may be significantly less
	Frequency of exposure at workplace [for one worker]	Once per day	For some applications/settings with shorter duration exposures, multiple exposures may occur in a

		single day
Annual amount used per site	10 kg/d	0.00005 (10% in region, plus 0.0005 fraction of main local source from HERA)
Emission days per site	365 d/y	Default for ERC8

Information on estimated exposure and Downstream-user guidance

3 Exposure estimation and reference to its source:

Dermal exposure estimates (based on ECETOC TRA model) for cleaning and maintenance

Process category	Description	Predicted exposure (µg/cm ² /day)	Exposed skin surface area (cm ²)	Dermal exposure (mg/kg/day) ^a
PROC8a	Transfer from/to large vessels (non-dedicated)	1000	960	13.7
PROC8b	Transfer from/to large vessels(dedicated)	1000	480	6.9
PROC9	Transfer to small containers	1000	480	6.9
PROC7	Industrial spraying	100	1500	2.14
PROC10	Roller application or brushing	2000	960	27.4
PROC13	Dipping or pouring	2000	480	13.7

(a) Calculated assuming a default bodyweight of 70 kg for workers

Inhalation exposure estimates (based on ECETOC TRA model) for cleaning and maintenance products	Process category	Description	Predicted exposure (µg/cm ² /day)	Exposed skin surface area (cm ²)	Dermal exposure (mg/kg/day) ^a
	PROC8a	Transfer from/to large vessels (non-dedicated)	0.063	0.5	0.07
	PROC8b	Transfer from/to large vessels (dedicated)	0.012	0.1	0.014
	PROC9	Transfer to small containers	0.012	0.1	0.01
	PROC7	Spraying in industrial settings and applications	0.63	5	0.71
	PROC10	Roller application or brushing	0.063	0.5	0.07
	PROC13	Dipping or pouring	0.012	0.1	0.014
	Summary of long-term exposure concentration to workers	Routes of exposure	Concentrations	Justification	
Dermal local exposure (in µg/cm ²)		12	ECETOC TRA prediction for PROC10; multiplied by a dermal uptake factor of 0.006.		
Dermal systemic exposure (in mg/kg bw/d)		0.16	ECETOC TRA prediction for PROC10; multiplied by a dermal uptake factor of 0.006.		
Inhalation exposure (in mg/m ³)/8h workday		5	ECETOC TRA prediction for PROC7		
Inhalation exposure (in mg/kg/d)/8h workday		0.71	ECETOC TRA prediction for PROC7		
4	Operational conditions related to available dilution capacity and characteristics of exposed humans				
Occupational exposure Operational conditions related to respiration and skin contact	Information type	Data field	Explanation		
	Respiration volume under conditions of use	10 m ³ /d	Default for workers, light activity		
	Area of skin contact with the substance under conditions of use	480 cm ² 1500 cm ² 960 cm ² 480 cm ² 480 cm ² 960 cm ² 1500 cm ² 480 cm ² 1980 cm ²	ECETOC TRA default: PROC5: PROC7: PROC8a: PROC8b: PROC9 PROC10 PROC11 PROC13 PROC19		
	Body weight	70 kg	Default for workers		

Operational conditions related to respiration, skin contact and ingestion for the general public	Information type	Data field	Explanation
	Skin contact area	960 cm ²	ConsExpo default
	Mouth contact area	-	Not applicable – no oral exposure
	Respiration volume under conditions of use	26 m ³	Default: Light activity 26 m ³ /24 h
	Room size and ventilation rate	20m ³ ; exchange per hour 0.6 h ⁻¹	ConsExpo defaults
	Body weight	65 kg	Default adult bodyweight
Predicted Exposure Concentrations of Environmental releases		PEC	unit
	AIR		
	Annual average local PEC in air (total)	1.30 x 10 ⁻¹⁵	[mg.m ⁻³]
	WATER, SEDIMENT		
	Local PEC in surface water during emission episode (dissolved)	2.48 x 10 ⁻²	[mg l ⁻¹]
	Annual average local PEC in surface water (dissolved)	2.48 x 10 ⁻²	[mg l ⁻¹]
	Local PEC in fresh-water sediment during emission episode	4.23 x 10 ⁻¹	[mg kg wwt ⁻¹]
	Local PEC in seawater during emission episode (dissolved)	2.37 x 10 ⁻³	[mg l ⁻¹]
	Annual average local PEC in seawater (dissolved)	2.37 x 10 ⁻³	[mg l ⁻¹]
	Local PEC in marine sediment during emission episode	4.05 x 10 ⁻²	[mg kg wwt ⁻¹]
	SOIL, GROUNDWATER		
	Local PEC in agric. soil (total) averaged over 30 days	4.02 x 10 ⁻¹	[mg kg wwt ⁻¹]
	Local PEC in agric. soil (total) averaged over 180 days	1.32 x 10 ⁻¹	[mg kg wwt ⁻¹]
	Local PEC in grassland (total) averaged over 180 days	5.27 x 10 ⁻²	[mg kg wwt ⁻¹]
	Local PEC in pore water of agricultural soil	1.99 x 10 ⁻³	[mg l ⁻¹]
	Local PEC in pore water of grassland	7.95 x 10 ⁻⁴	[mg l ⁻¹]
	Local PEC in groundwater under agricultural soil	1.99 x 10 ⁻³	[mg l ⁻¹]

Substance / User identity		
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	6. Use in paper
	Processes and activities covered by the exposure scenario	SU3, SU6 PROC 5, PROC 8a
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	solid
	Concentration of substance in preparation or article	
	Other relevant operational conditions of use	N/A
Risk management measures:		
2.1	Control of worker exposure	Following the REACH descriptor system, the following product type is covered by this generic scenario: Paper and board dye, finishing and impregnation products: including bleaches and other processing aids (PC26).
	Technical conditions and measures at process level (source) to prevent release	N/A
	Technical conditions and measures to control dispersion from source towards the worker	N/A
	Engineering controls:	N/A
	Organisational measures to prevent/limit releases, dispersion and exposure	N/A
	Conditions and measures related to personal protection, hygiene and health evaluation	N/A
	2.2	
Control of environmental exposure		
Frequency and duration of use		
Waste water flow	N/A	
Dilution factor	N/A	
Emission factor to waste water	N/A	
Release fraction	N/A	
Conditions and measures related to external recovery of waste	N/A	
Information on estimated exposure and Downstream-user guidance		
3	Exposure estimation and reference to its source:	
		N/A
4	Guidance to DU to evaluate whether he works inside the boundaries set by the ES	
	Occupational exposure	N/A
	Environmental emissions	Citric acid is used in the cleaning of papermaking machines and to prevent build up of deposits. It is added to the pulp slurry prior to bleaching to control paper staining by sequestering metal ions. Cleaning applications are covered under another exposure

		<p>scenario; this document covers use of citrate as a processing aid in the paper-making industry.</p> <p>This generic scenario makes use of the following documents:</p> <p style="padding-left: 40px;">OECD Emission Scenario Documents on Kraft, Non-Integrated and Recovered Pulp Mills.</p> <p>This covers the use of citrate as a process aid in the paper-making industry. It is possible that a small amount of citrate is incorporated into the finished paper products. However, it is considered that the amount of citrate that ends up in articles and could be released (resulting in consumer exposure) is likely to be negligible.</p> <p>The amount of citric acid believed to be used in this application is at most 1000 tpa. The industrial use per site is unknown. However, a default approach would be to consider 10 paper mills in a single region, operating over 300 days per year. The substance is not mixed into pulp, but is applied to machinery. A loss of 2% is a realistic maximum.</p> <p>This gives a daily release of</p> $100 \text{ t} \times 1000 \text{ kg/t} \times 0.02 / 300 \text{ d} = 6.7 \text{ kg/d}$ <p>For the environment, the amounts passing to waste are very likely to be less than those from the ES 1-5. Therefore there is no need to complete an exposure assessment at a local scale with full details of PEC values etc.</p> <p>However, a regional release of 67 kg/d to waste water will be added to the model.</p> <p>For human health worker exposure at paper mills will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.</p>
--	--	---

Substance / User identity		
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	7. Use in construction
	Processes and activities covered by the exposure scenario	SU3, SU21, SU22, SU2, SU10, SU19, PROC 2, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 11. PROC 13, PROC 14, PROC 19, PROC 21, PROC 24
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	solid
	Concentration of substance in preparation or article	N/A
	Other relevant operational conditions of use	N/A
Risk management measures:		
2.1	Control of worker exposure	<p>Following the REACH descriptor system, the following product types are covered by this generic scenario: PC10 (Building and construction preparations not covered elsewhere).</p> <p>The following substances are used in construction materials: citric acid and trisodium citrate.</p> <p>Citrates can be used to retard the setting rate of cement and reduce the amount of water needed. They may therefore be added to concrete, mortar, plaster and render formulations. The concentration in these products is generally low (<1%).</p>
	Technical conditions and measures at process level (source) to prevent release	N/A
	Conditions and measures related to personal protection, hygiene and health evaluation	N/A
2.2	Control of environmental exposure	
	Frequency and duration of use	
	Use per site Duration of emission Waste water flow Dilution factor	N/A
	Emission factor to waste water Release fraction	N/A
	Environment factors not influenced by risk management	N/A
	Other given operational conditions affecting environmental exposure	
	Technical conditions and measures at process level (source) to prevent release	No specific measures are considered.
	Technical onsite conditions and measures to reduce or limit discharges,	N/A

	air emissions and releases to soil	
	Organizational measures to prevent/limit release from site	N/A
	Conditions and measures related to municipal sewage treatment plant	N/A
	Conditions and measures related to external treatment of waste for disposal	N/A
	Conditions and measures related to external recovery of waste	none
Information on estimated exposure and Downstream-user guidance		
3	Exposure estimation and reference to its source:	
	Occupational exposure: Dermal Inhalation	N/A
4	Guidance to DU to evaluate whether he works inside the boundaries set by the ES	
	Occupational exposure	N/A
	Environmental emissions	<p>This document provides an environmental generic exposure scenario for substances used in construction materials. This generic scenario makes use of the following documents:</p> <p style="padding-left: 40px;">EU Technical Guidance Document (TGD) emission scenario document. REACH Technical Guidance.</p> <p>The amount of citric acid believed to be used in this application is at most 1500 tpa. The industrial use per site is unknown, but should be considered as a widely dispersed use. In the worst case a release of the entire tonnage to the region could be included, i.e. 1500 tpa. Of this, part will be released to industrial soil (90%) and part to waste water (10%).</p> <p>A regional release of $150 \times 1000/365 = 411$ kg/d to waste water will be added to the model, and 3699 kg/d to industrial soil will be included.</p> <p>For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.</p>

Substance / User identity		
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	8. Use in polymers and plastics
	Processes and activities covered by the exposure scenario	SU3,SU11,SU12, PROC 3, PROC 5, PROC 8a, PROC 8b
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Physical form of substance: under conditions of use it is used as a liquid.	solid
	Concentration of substance in preparation or article	N/A
	Other relevant operational conditions of use	<p>Please also note that under acidic conditions (pH<7), sulfur dioxide can be formed. Please ensure compliance with the existing occupational exposure limit as recommended by SCOEL (2008) for sulfur dioxide of 0.5 ppm (TWA, 8h) respectively 1 ppm (STEL, 15 min).</p> <p>Polyolefin foams are used for a variety of applications such as automotive, construction, food packaging, sport and leisure, and many other industrial and consumer uses. They usually have a high strength to weight ratio and are manufactured in a variety of processes and in low density (25 - 250 kg/m³) or high density (250 - 700 kg/m³) versions, or even in densities as low as 16 kg/m³ for polystyrene. All current extrusion processes involve the following steps: melting, mixing with blowing agents, cooling of melt, expansion and degassing/aging. The steps in this process can be realized in different configurations of equipment, e.g., with long single-screw extruders, twin-screw extruders, or tandem extruder lines.</p> <p>Both citric acid (or citrate salt) and (bi)carbonate may be surface-treated with, for example, a fatty acid ester to make them compatible with the polyolefin. A concentrated master batch of the formulated foaming agent in polymer at loading levels of from about 5% to about 50% actives may then be prepared. The master batch is added to the polymer melt which is to be foamed such that the blowing agents are at 0.1 to 2.0% active levels in the final formulation [US 5,302,455 and refs. therein].</p> <p>By-products of this reaction are mono-, di-, and/or trisodium citrate, in combination with other sodium salts, which will still be present within the foamed polymer. These residues are typically present at around 50 wt.% of the initial foaming agent formulation, which is equivalent to <1 wt.% of the total foamed polymer in most cases [RAPRA, 2004].</p>
Risk management measures:		
2.1	Control of worker exposure	
	Technical conditions and measures at process level (source) to prevent release	N/A
	Technical conditions and measures to control dispersion from source towards the worker	N/A
	Engineering controls:	
	Organisational measures to prevent/limit releases, dispersion and exposure	N/A

	Conditions and measures related to personal protection, hygiene and health evaluation	
2.2	Control of environmental exposure	
	Use per site Duration of emission Waste water flow Dilution factor	N/A
	Release of citric acid	<p>Losses from conversion, service life and disposal for chemical blowing agents are considered to be zero as the additive is destroyed during the conversion process.</p> <p>Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at 10 sites across Europe, the local losses to water air and solid waste are:</p> <p>The REACH defaults for ERC6d are for the production on 300 days per year if the tonnage of the product is >5000 tpa [ECHA, 2009]. Citrate is present at <1% in plastics applications (see Section 2.1.1), therefore, the total production volume is approx. 100,000 tpa. Therefore, the maximum daily releases are as follows:</p> <p>Water: $20 \text{ t} \times 1000 \text{ kg/t} \times (0.0065) / 300 = 0.43 \text{ kg/d}$</p> <p>Air: 0</p> <p>For the environment, the amounts passing to waste are very likely to be less than those from the ES 1-5. Therefore there is no need to complete an exposure assessment at a local scale with full details of PEC values etc.</p> <p>However, a regional release of 0.35 kg/d to waste water will be added to the model, and similarly 3.18 kg/d to the continental scale.</p>
	Environment factors not influenced by risk management	N/A
	Other given operational conditions affecting environmental exposure	N/A
	Technical conditions and measures at process level (source) to prevent release	N/A
	Conditions and measures related to external recovery of waste	none
	Information on estimated exposure and Downstream-user guidance	
3	Exposure estimation and reference to its source:	
	Occupational exposure: Dermal Inhalation	Not relevant
4	Guidance to DU to evaluate whether he works inside the boundaries set by the ES	
	Occupational exposure	For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.
	Environmental emissions	N/A

Substance / User identity		
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	9. Use in the oil industry
	Processes and activities covered by the exposure scenario	SU3 , SU2 PROC 3, PROC 4, PROC 5,
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Physical form of substance: under conditions of use it is used as a liquid.	solid
	Concentration of substance in preparation or article	20-50%
	Other relevant operational conditions of use	<p>In the oil industry, citric acid is often used for oil-well acidizing to prevent the formation of insoluble iron precipitates [APAC]. Oil well acidizing is the term used for the application of hot hydrochloric acid (200-300°F) to dissolve scale and other deposits from the wellbore [McGraw-Hill].</p> <p>Oxidation reactions, which occur in wells injected with HCl, cause formation of insoluble iron precipitates. These precipitates can plug the wellbore and pumping operations are thus interrupted by these gels, and hence, citric acid is added to the acid solution to prevent gel formation [APAC].</p> <p>Oil producing well formations can become plugged with acid soluble minerals and restrict oil production [Gewanter, Herman L. et al]. Production can be increased by forcing acid down the wellbore to dissolve the minerals [Gewanter, Herman L. et al]. The acids readily dissolve the iron and iron containing minerals in the wellbore casing and the formation [Gewanter, Herman L. et al]. However, water and carbonates will precipitate from the acid solution, which allows for the re-precipitation of the iron to ferric hydroxide above a pH of 4 [Gewanter, Herman L. et al]. Certain chemicals must be added at this point to maintain it in a soluble state [Gewanter, Herman L. et al].</p>
Risk management measures:		
2.1	Control of consumers exposure	Not relevant
	Human factors not influenced by risk management	Not relevant
	Other given operational conditions affecting consumers exposure	Not relevant
	Conditions and measures related to information and behavioural advice to consumers	Not relevant
	Conditions and measures related to personal protection, hygiene and health evaluation	Not relevant
2.2	Control of environmental exposure	
	Frequency and duration of use	
	waste water Release	<p>Control of the re-precipitation of iron and the pH, as the acid is spent, can be achieved by the sequestration by organic chelants and the reduction to soluble ferrous iron [Gewanter, Herman L. et al]. Citric acid is a useful organic chelant and is used for this purpose [Gewanter, Herman L. et al]. Other chelants may include gluconic acid, the tetrasodium salt of ethylenediaminetetraacetic acid (EDTA), and the trisodium salt of nitrilotriacetic acid (NTA) [Gewanter, Herman L. et al].</p> <p>This is a widely dispersed use but in the worst case it can be envisaged that the entire tonnage could pass to surface marine water. This equates to</p>

		100 t x 1000 kg/t /365 = 274 kg/d to the regional surface water 900 t x 1000 kg/t /365 = 2740 kg/d to the continental surface water
	Environment factors not influenced by risk management	None
	Conditions and measures related to external treatment of waste for disposal	None
	Conditions and measures related to external recovery of waste	none
Information on estimated exposure and Downstream-user guidance		
3	Exposure estimation and reference to its source:	
	Human exposure:	For human health worker exposure at oil production sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.
4	Guidance to DU to evaluate whether he works inside the boundaries set by the ES	
	Consumer exposure	N/A
	Environmental emissions	N/A

Substance / User identity				
	Registration number(s)	01-2119457026-42-0004		
	Substance identity	CAS#77-92-9; EC#201-069-1		
1	Short title of the exposure scenario	10. Use in textiles		
	Processes and activities covered by the exposure scenario	SU3,SU5 PROC8a,PROC8b, PROC10, PROC13, PROC22		
2	Operational conditions and risk management measures			
	Duration an frequency of use			
	Worker All applicable PROCs	>4h		
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.		
	Concentration of substance in preparation or article			
	Other relevant operational conditions of use	<p>No measured data are available for releases of citric acid to air and waste water from textile production sites. Releases are therefore estimated on the basis of information in the public domain.</p> <p>Potential exposure to humans and especially the environment is dependent on the intended function of the substance, as well as the substrates and processes used. Functional finishing agents and other chemically reactive substances are intended to be consumed during use, therefore the amount released is related to efficiency of the process. On the other hand, non-reacting substances (e.g. processing aids) are not consumed and will ultimately be lost to air or waste water, depending on their function and physicochemical properties. In virtually all cases, it is expected that citric acid or citrate salts, as process aids, will be lost to waste water.</p> <p>The annual tonnage of 300 t is considered to be used at 40% in the region. The largest site is estimated to use around 6 tpa. If all passed to waste water this is:</p> $6 \text{ t} \times 1000 \text{ kg/t} / 300 = 20 \text{ kg/d.}$		
Risk management measures:				
2.1	Control of worker exposure	For human health worker exposure at textile production sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.		
	Risk management measures for industrial site	Information type	Data field	Explanation
		Onsite pre-treatment of waste water	Yes	Neutralisation
		Resulting fraction of initially applied amount in waste water released from site to the external sewage system		On-site biological waste treatment (where present) is expected to remove a high proportion of citric acid, as the substance is highly biodegradable. However, on-site biological waste treatment is not assumed as it is not known that this is always present.
		Air emission abatement	No measured data	
Resulting fraction of applied amount in waste	No waste gases			

		gas released to environment		
		Onsite waste treatment	No measured data	Secondary biological treatment may be present but this is not assumed in the scenario
		Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment.	No measured data	
		Municipal or other type of external waste water treatment	None	None
		Effluent (of the waste water treatment plant) discharge rate	2000000 l/d	Default for a standard WWTP
		Recovery of sludge for agriculture or horticulture	Yes	
	Personal protective equipment (PPE)	N/A		
	Other risk management measures related to workers	N/A		
2.2	Control of environmental exposure			
	Frequency and duration of use			
	Duration, frequency and amount			
Information on estimated exposure and Downstream-user guidance				
3	Exposure estimation and reference to its source:			
	Releases to air	As the citrates are solids with high water solubility, losses to air are considered to be negligible.		
	Releases to waste water	Citric acid and citrates are used in textile and leather treatment in aqueous solution. The most likely release route will be to waste water via spillage, clean out and discharge of spent treatment baths and liquors recovered in handling fabrics after treatment. Indeed, releases to waste water can be assumed to be 100%, since all the citric acid/citrate may be washed to drain.		
	Technical fate of substance and losses from process/use to waste, waste water and air	Information	Data field	Explanation
		Fraction of applied amount lost from process/use to waste gas	0 kg/kg	See text
		Fraction of applied amount lost from process/use to waste water	1 kg/kg	See text

Predicted Exposure Concentrations of Environmental releases	PEC	unit
	AIR	
Annual average local PEC in air (total)	1.56 x 10 ⁻¹⁵	[mg.m ⁻³]
WATER, SEDIMENT		
Local PEC in surface water during emission episode (dissolved)	2.92 x 10 ⁻²	[mg l ⁻¹]
Annual average local PEC in surface water (dissolved)	2.67 x 10 ⁻²	[mg l ⁻¹]
Local PEC in fresh-water sediment during emission episode	4.98 x 10 ⁻¹	[mg kg wwt ⁻¹]
Local PEC in seawater during emission episode (dissolved)	1.01 x 10 ⁻¹	[mg l ⁻¹]
Annual average local PEC in seawater (dissolved)	8.35 x 10 ⁻²	[mg l ⁻¹]
Local PEC in marine sediment during emission episode	1.73	[mg kg wwt ⁻¹]
SOIL, GROUNDWATER		
Local PEC in agric. soil (total) averaged over 30 days	5.87 x 10 ⁻¹	[mg kg wwt ⁻¹]
Local PEC in agric. soil (total) averaged over 180 days	1.93 x 10 ⁻¹	[mg kg wwt ⁻¹]
Local PEC in grassland (total) averaged over 180 days	7.70 x 10 ⁻²	[mg kg wwt ⁻¹]
Local PEC in pore water of agricultural soil	2.91x 10 ⁻³	[mg l ⁻¹]
Local PEC in pore water of grassland	1.16 x 10 ⁻³	[mg l ⁻¹]
Local PEC in groundwater under agricultural soil	2.91 x 10 ⁻³	[mg l ⁻¹]
Exposure concentration in sewage treatment plants (STP)	<p>No measured data are available for the concentration of citric acid in sewage treatment plants (STP). The concentration of the citrate has been estimated using EUSES 2.1.1. The EUSES model uses the Simple Treat sewage treatment model to predict the fate of a substance in the STP, based on the physicochemical and biodegradation properties. For citric acid, SimpleTreat predicts the following:</p> <p>12.6 % to water: 0.112 % to air: 0.0154 % to sludge: 87.3 % degraded.</p> <p>Sludge from WWTPs may be spread on agricultural soil.</p>	

Substance / User identity		
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	11. Use in paints and coatings
	Processes and activities covered by the exposure scenario	SU3, SU21, SU22, SU17, SU18, SU19 PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 19, PROC 21, PROC 24
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	Other relevant operational conditions of use	N/A
Formulation of exposure scenario:		
2.1	Formulation of exposure scenario	<p>A paint factory formulating 10000 tpa of formulated paint could need around 10000 x 0.001 = 10 tpa of citric acid. Paint formulation is a widespread activity and this estimate is consistent with a total market size of 300 tpa.</p> <p>It is taken that the regional tonnage is 40 tpa.</p> <p>Assuming a worst case of 2% handling loss this is a local release of 200 kg per year. Such a wastage rate is less than for scenarios considered earlier and there is no need to calculate local exposures. The releases will be added as regional and continental losses to waste water:</p> <p>Regional = $200 \times (40/10) / 365 = 2.2 \text{ kg/d}$</p> <p>Continental $2.2 \times (260/40) = 14.3 \text{ kg/d}$</p>
	Use	<p>The coating process used by both professionals and consumers is typically by brush or roller application. For releases to waste water during consumer use, the OECD Emission Scenario Document for coatings assumes that an estimated 1% of the volatile fraction of the coating will be lost as brush residues and then end up in the sewer. The same fraction (1%) of the volatile fraction is assumed to be lost during professional use, but this is properly disposed and does not end up in the sewer [OECD, 2007].</p> <p>Therefore the amount of citric acid in the application passing to waste is estimated to be widely dispersed:</p> <p>Regional wastewater:</p> <p>$0.1 \times 300 \text{ tpa} \times 1000 \text{ kg/t} \times 0.01 / 365 = 0.82 \text{ kg/d}$</p> <p>Continental wastewater:</p> <p>$0.9 \times 300 \text{ tpa} \times 1000 \text{ kg/t} \times 0.01 / 365 = 7.40 \text{ kg/d}$</p>

		<p>Therefore, for simplicity, for this application area, the totals are:</p> <p>Regional wastewater:</p> <p>+ 0.82 = 3.0 kg/d</p> <p>Continental wastewater:</p> <p>14.3 + 7.4 = 21.7 kg/d</p> <p>For human health worker exposure at paint production sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.</p>
--	--	--

Substance / User identity		
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9 ,EC#201-069-1
1	Short title of the exposure scenario	12、 Use in photography
	Processes and activities covered by the exposure scenario	SU20,SU21,SU22 PROC5, PROC 13
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	Other relevant operational conditions of use	N/A
Formulation of exposure scenario:		
2.1	Exposure scenario	<p>Citric acid is one of a range of complexing agents used in photography to control the effects of calcium and magnesium hardness, and to keep iron soluble in solution as part of redox processes.</p> <p>Due to the rapid growth of digital photography, use of chemicals in film processing is now limited almost entirely to a small number of professional providers. The chemicals used are collected by photochemical companies in order to recover silver and disposal to drain does not take place.</p> <p>Citrate may also be used as a stop bath in professional or consumer settings as part of the process for the manual development of photographic film. Releases to the environment from this application are insignificant compared to those from considered in other exposure scenarios (cleaning products for example).</p> <p>Therefore this scenario need not be considered further in respect of the environment.</p>
	human health	<p>For human health, the processes applied during both professional and consumer uses are:</p> <p>PROC 9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC 5 Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC 13 Treatment of articles by dipping and pouring</p>

Substance / User identity		
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	13. Use in paints and coatings
	Processes and activities covered by the exposure scenario	SU3 PROC 1, PROC 2, PROC 4, PROC 8a
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	relevant operational conditions of use	<p>Following the REACH descriptor system [ECHA, 2009] the following sector of use is covered by this scenario: SU3 Industrial uses</p> <p>The relevant product category is PC21 Laboratory chemicals</p> <p>Citric acid may be used at low levels within laboratories. Exposures will take place but under highly controlled conditions. Therefore this scenario need not be considered further for human health or the environment.</p>

Substance / User identity		
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	14. Use in water treatment
	Processes and activities covered by the exposure scenario	SU3, SU14, SU15, SU16, SU17, PROC 1, PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 13, PROC 17, PROC 18, PROC 20, PROC 23, PROC xyz ¹
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	relevant operational conditions of use	This scenario covers use in smaller-scale circulating water treatment in industrial settings, which typically use high substance concentration at low discharges and would usually have a waste water treatment plant (WWTP) in place. The degradability of citric acid in power station cooling systems makes in not suitable for such purposes.
Formulation of exposure scenario:		
2.1	Industrial cooling systems	<p>Industrial cooling systems can be categorized by their design and by using water as coolants. The exchange of heat between process medium and coolant is enhanced by heat exchangers. From the heat exchangers the coolant transports the heat into the environment.</p> <p>Usage of water treatments containing citrates would be continuous for the correct functioning of the cooling water system. Re-loading may be needed more or less frequently, for open and closed cooling water systems respectively, to refresh the system.</p> <p>The worst-case for the local environment is to assume treatment of a large industrial plant, open cooling system, which requires the use of large volumes of a high concentration product on a continuous basis and involves the direct release of blow down effluent to the river or receiving water.</p>
	In open recirculating systems	<p>In open recirculating systems, alkaline conditions (pH of 8-9), in combination with organic complexing agents are effective against corrosion and scaling. Most currently used corrosion programmes are based on phosphates, and zinc is added if water conditions require this.</p> <p>Typical concentrations of scale control agents (polyphosphates, phosphonates, polyacrylates, copolymers and ter-polymers) range from 2 to 20 mg/l, as active compound. Hardness stabilisers prevent the formation of crystals and are used in recirculating systems, but rarely or never in once-through systems. Citrates may be used to enhance the performance of the other additives.</p> <p>In most downstream uses treatment chemicals are applied in water-based processes. The final concentration in the water used in scale inhibition is typically from less than 1 to 10 ppm. Depending on the exact nature of the process, the complexing agents may remain present in the aqueous effluent and the discharge streams. These streams will be treated on the user's site, discharged to sewer systems or discharged to waterways</p>

		<p>(wide dispersive use).</p> <p>Given the low volatility and the high water solubility of the substances, direct releases to air and soil can be considered negligible.</p>
	Wastewater	<p>In the UK, the capacity of 50% of installed base cooling towers is in the range of 22.7 m³ and 227 m³ (OECD, 2004). The water circulation rate of a typical open cooling system (with capacity of 100 m³), for an industrial plant, is assumed to be 350 m³/h (3.5 times the capacity). The blowdown of open cooling systems is related to the rate of evaporation (1% of the circulation rate) and the concentration cycle, which is the ratio (typically 3) of the maximum concentration of dissolved solids in the recirculating water to the concentration in the make up water (OECD, 2004).</p> <p>For the purpose of this calculation, a scaling inhibitor product with an active content of citrate at 25% is assumed.</p> <p>Therefore, for a blowdown of 1.75 m³/h from an open cooling system; the estimated release of citrates to water is</p> $0.25 \times 20 \text{ mg/l} \times 1.75 \text{ m}^3/\text{h} \times 1000 \text{ l/m}^3 \times 24 \text{ h/d} \times 10^{-6} \text{ kg/mg}$ $= 0.44 \text{ kg/day.}$ <p>This is lower than ES considered above and there is therefore no need to develop the scenario further.</p> <p>In the nature of the use it must be assumed that all the citric acid used in water treatment could pass to waste water. Therefore:</p> <p>Regional wastewater:</p> $0.1 \times 1000 \text{ tpa} \times 1000 \text{ kg/t} / 365 = 274 \text{ kg/d}$ <p>Continental wastewater:</p> $0.9 \times 1000 \text{ tpa} \times 1000 \text{ kg/t} \times /365 = 2470 \text{ kg/d}$
	human health	<p>For human health worker exposure at industrial sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.</p>

Substance / User identity		
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	15. Use in metal surface treatment
	Processes and activities covered by the exposure scenario	SU3, SU14, SU15, SU16, SU17, SU21, SU22 PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 13, PROC 17, PROC 18, PROC 23
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	relevant operational conditions of use	Citric acid may be used as a complexing agent during metal surface treatment operations. This includes cleaning, brightening and passivation of fabricated stainless steel components, and other metal components, cleaning of circuit boards prior to soldering, and metal cleaning or chemical polishing for the surface treatment of aluminium, copper and other metals. The following applications should be taken as representative rather than the sole example of where and why citric acid or citrates may be used in the treatment of metal surfaces. Some industries using citric acid include fasteners, medical devices, semi-conductors, automotive and aerospace.
	Passivation	Citric acid may be used in stainless steel passivation to remove iron from the surface of the stainless steel and prevent later corrosion. After thorough cleaning, the stainless steel part is immersed in a passivating acid bath. Any one of three approaches can be used: nitric acid passivation, nitric acid with sodium dichromate passivation and citric acid passivation. Which approach to use depends on the grade of stainless steel and prescribed acceptance criteria. When citric acid passivation is used, typical solutions range from 4 to 10% citric acid by weight.
Electroless plating	<p>Plating describes the coating of surfaces with metals, either through an electrolysis or electroless plating processes. Electroless plating is also known as 'autocatalytic' plating; deposition of the metal starts on metal nuclei such as palladium and continues autocatalytically. Electroless plating is favoured over electrolysis for most component production (EA 2009).</p> <p>There are usually three stages in the electroless plating process: de-smearing, activation and electroless copper plating. The plating solution has a copper content of 2 – 5 g/l, with sodium hydroxide (15 – 20 g/l), complexing agents (10 – 15 g/l) or tartrates (5 – 10 g/l) and reducing agents, such as formaldehyde (3 – 5 g/l). The process solution lifetime is limited by the build-up of reaction products and is proportional to the rate of throughput of components (EA 2009). Citrate may be used as a complexing agent.</p> <p>Electroless plating involves the large-scale use of water in both providing the medium for the process itself and for the subsequent rinsing and washing of components. There is a degree of recycling of rinse water through use to top-up the plating tanks, but there is ultimately loss through carry-over on components. Spent fluids can only be topped up a limited number of times before the media needs replacing. Water-soluble waste is discharged in waste water for basic on-site treatment (settling and pH adjustment) before discharge to municipal treatment works, controlled by local discharge consent</p>	

		agreements (EA 2009).
Exposure scenario:		
2.1	Environment exposure	The use of citrate in metal-surface treatment is estimated as approx. 1000 tpa. Therefore, environmental releases are not dissimilar to those discussed in the cleaning scenario (ES5) but on a much smaller scale. Therefore, it is not considered necessary to further assess environmental exposure.
	human health	For workers, exposures are not expected to be greater than those discussed in other industrial use scenarios. The basic risk management measures discussed for these scenarios are considered sufficient to ensure safe use. Human health exposure is not discussed further.

Substance / User identity		
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	16. Use in agriculture
	Processes and activities covered by the exposure scenario	SU1, SU3, SU21, SU22 PROC 3, PROC 5, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 14, PROC 15, PROC 19
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	relevant operational conditions of use	This scenario covers use in smaller-scale circulating water treatment in industrial settings, which typically use high substance concentration at low discharges and would usually have a waste water treatment plant (WWTP) in place. The degradability of citric acid in power station cooling systems makes in not suitable for such purposes.
Formulation of exposure scenario:		
	Wastewater	The amount of citric acid believed to be used in this application is at most 1500 tpa. The use per site is unknown, but this should be considered as a widely dispersed use. In the worst case a release of the entire tonnage to the region could be included, i.e. 1500 tpa. Of this, part will be released to agricultural soil (90%) and part to waste water (10%). A regional release of $150 \times 1000/365 = 411$ kg/d to waste water will be added to the model, and 3699 kg/d to soil will be included.
	human health	For human health worker exposure will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.

Substance / User identity		
	Registration number(s)	01-2119457026-42-0004
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	17. Use in medical devices
	Processes and activities covered by the exposure scenario	SU3, SU20, SU22 PROC 1
2	Operational conditions and risk management measures	
	Duration and frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	relevant operational conditions of use	Citrates may be used in medical devices, for example, citrate is added to human blood to prevent coagulation. The whole blood collection process is a closed process as sterility must be maintained. Procedures are carried out by trained personnel in a controlled environment. Therefore, exposures from this use are expected to be minimal and the scenario is not considered further for human health or the environment.

Substance / User identity						
	Registration number(s)	01-2119457026-42-0004				
	Substance identity	CAS#77-92-9; EC#201-069-1				
1	Short title of the exposure scenario	18. Regional exposure concentrations				
	Processes and activities covered by the exposure scenario	N/A				
2	Regional exposure concentrations					
		Predicted regional Exposure Concentrations		Measured regional exposure concentrations		Explanation / source of measured data
		value	unit	value	unit	
	Freshwater	1.52 x 10 ⁻²	mg/l	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1
	Marine water	1.41 ⁻³	mg/l	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1
	Freshwater sediments	3.32 x 10 ⁻¹	mg/kg d.w.	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1
	Marine sediments	2.60 x 10 ⁻²	mg/l	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1
	Agricultural soil	3.19 x 10 ⁻³	mg/kg wwt	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1
	Grassland	7.47 x 10 ⁻¹²	mg/kg wwt	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1
	Air	1.24 x 10 ⁻¹⁹	(mg/m ³)	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1

DISTRIBUTOR COMPANY INFORMATION			
name	BRENNTAG N.V.	BRENNTAG Nederland B.V.	BRENNTAG SOUTH AFRICA (PTY) LTD
address	Nijverheidslaan 38 8540 Deerlijk	Donker Duyvisweg 44 3316 BM Dordrecht	11 Mansell Road Killarney Gardens, 7441
country	Belgium	The Netherlands	South Africa
phone number	+32 (0)56 77 69 44	+31 (0)78 65 44 944	+27 (0)21 0201800
website	www.brenntag.be	www.brenntag.nl	www.brenntag.co.za
e-mail	info@brenntag.be	info@brenntag.nl	info@brenntag.co.za
activities	Distribution and export of chemicals and ingredients		
VAT number	BE0405317567	NL001375945B01	4740102209
emergency number(24/365)	+32 (0)56 77 69 44	+31 (0)78 6544 944	+27 (0)21 0201800
management systems: certifications	ISO 9001, ISO 14001, ISO 22000, FSSC 22000, GMP+ Feed, ESAD	ISO 9001, ISO 14001, ISO 22000, FSSC 22000, OHSAS 18001, GMP+ Feed, ESAD, AEO	ISO 9001, FSSC 22000